EXHIBIT G

South Carolina State Housing Finance and Development Authority 2018 Architect and/or Professional Engineer Certification

Development Name:		I otal # of Bldgs. In the project:			
		Low Income	e Units		
Unit Type:	# of Units:	# of Baths:	Heated Area:	Total Heated Area:	
Efficiency			s.f.	s.f.	
1 Bedroom			s.f.	s.f.	
2 Bedroom			s.f.	s.f.	
3 Bedroom			s.f.	s.f.	
4 Bedroom			s.f.	s.f.	
Living Units Total:		Sub-Total I	Residential Heated Sq. Ft.:	s.f. (A)	
Type:	# of Type:		Area:	Total Area:	
Covered Porches			s.f.	s.f.	
Breezeways Outside Storage			s.f. s.f.	s.f.	
Other:			s.r. s.f.	s.f. s.f.	
<u> </u>		тс	TAL NON-HEATED AREA:	s.f.	
		Mandad Dat	11		
Unit Type:	# of Units:	Market Rate # of Baths:	e Units Heated Area:	Total Heated Area:	
Unit Type: Efficiency			s.f.		
1 Bedroom			s.i. s.f.	s.f. s.f.	
2 Bedroom					
3 Bedroom			s.f.	s.f.	
4 Bedroom			s.f.	s.f.	
Living Units Total:		Sub-Total I	s.f. Residential Heated Sq. Ft.:	s.f. (B)	
Living Office Total.		Sub-10tal i	Nesidentiai neated 54. Ft	S.I. (D)	
Type:	# of Type:		Area:	Total Area:	
Covered Porches			s.f.	s.f.	
Breezeways Outside Storage			s.f.	s.f.	
Other:			s.f. s.f.	s.f.	
<u> </u>		тс	TAL NON-HEATED AREA:	s.f.	
		COMMON A	DEAC		
Office Area:		COMMON F	s.f.	s.f.	
Laundry:			s.f.	s.f.	
Exercise Room:			s.f.	s.f.	
Computer Room:			s.f.	s.f.	
Community Building:			s.f.	s.f.	
Other:			s.f.	s.f.	
		Sub-Total Non-	Residential Heated Sq. Ft.:	s.f. (C)	
		ΤΩΤΔ	HEATED AREA (A+B+C):	s.f.	

NOTE: All square footages listed on Exhibit G must match those listed in the tax credit application. All heated and non-heated square footage for the entire development must be included on this form and on any submitted drawings.

MANDATORY DESIGN CRITERIA

The development <u>will be</u> designed and constructed incorporating the following **Mandatory Design Criteria** included at no extra cost to the tenants.

For All Development Types:

- 1. Window coverings for each window, including glass doors, must be installed. Metal blinds are not permitted.
- 2. All kitchen and bathroom interior cabinets must be solid wood or wood/plastic veneer products with dual slide tracks on drawers. New cabinets must have solid wood dual sidetrack drawers and no laminate or particleboard fronts for doors or drawer fronts. Cabinets shall meet the ANSI/KCMA A1 61.1 performance and construction standard for kitchen and vanity cabinets. Cabinets shall bear the certification seal of KCMA (Kitchen Cabinet Manufacturers Association).
- 3. All entry doors must be metal-clad wood, steel or fiberglass doors that are insulated, paneled, and have a peephole. Deadbolt locks are required in entry doors. Dead bolt locks on entry doors should have "thumb latch" on interior side. Double keyed dead bolt locks are prohibited. The minimum clear width of all exterior doors shall be 34 inches.
- 4. Bi-fold and sliding interior doors are prohibited. All doors must be side hinged.
- 5. A landscaping plan must be submitted indicating areas to be sodded and landscaped. Landscaping plan(s) must follow any applicable landscape municipal ordinance. At a minimum, sod shall be installed on the front and side areas to a point twenty (20'-0") feet from the building(s). Landscaping may incorporate sod and drought resistant plants and shrubs. All disturbed areas not sodded must be seeded. The Authority reserves the right to approve the final landscaping installation and require modifications.
- 6. All retention and/or detention ponds must be fenced in unless a letter is provided from the Department of Health and Environmental Control (DHEC) that a fence is not required. The storm water retention/detention basin design, maintenance and management shall be the sole responsibility of the owner/developer and shall be in strict accordance with all applicable federal, state, local and environmental regulations governing storm water retention/detention basins.
- 7. A recreation area suitable for proposed tenant targeting:
 - a. For family developments (i) Playground for children <u>located away from automobile traffic patterns</u> with commercial quality play equipment (the playground area must have a minimum of four (4) separate pieces of equipment or a structure that encompasses a minimum of four (4) pieces of equipment) accessible to handicapped traffic and at least one permanently anchored, weather resistant bench, with a back, or (ii) an exercise room with a minimum of three nautilus-type work-out machines (this room's square footage may be included in the minimum 1,200 sq. ft. community building);
 - b. For older persons developments (i) An exercise room with a minimum of three (3) nautilus type work-out machines (this room's square footage may be included in the minimum 1,200 sq. ft. community building), or (ii) a minimum of one gazebo that is covered, with bench seating, equipped with an Energy Star ceiling fan with light fixture.
- 8. A new development sign at the entrance(s) to the complex affixed with a Fair Housing logo.
- 9. Exterior lighting fixtures at all entry doors including individual apartment units, community buildings, and common areas within the building(s). Fixtures at the individual apartment units are to be controlled from the interior of the unit.
- 10. Enclosed trash dumpsters and/or compactors. The dumpster must be enclosed by solid fencing on at least three sides. The pad and approach pad to the dumpster must be concrete and not asphalt. The trash dumpster/compactor must be ADA accessible and located on an ADA accessible route.
- 11. Roofing materials shall be anti-fungal shingles with a minimum 25-year warranty.
- 12. The following Energy Star appliances must be provided in each unit: Full sized refrigerator-freezer, with ice maker, having a minimum size of fourteen (14) cubic feet.
- 13. At least fourteen (14) SEER HVAC units must be installed. If the Physical Needs Assessment, completed for a rehabilitation development, does not recommend replacement of existing HVAC units in the development, this mandatory criterion is waived. However, any replacement HVAC units installed in the development must be at least fourteen (14) SEER. All refrigeration lines must be insulated. All developments must have central heat and air. Window units are not allowed for any development type.
- 14. A laundry facility containing: (a) at least one (1) commercial washer and one (1) commercial dryer per twenty-four (24) units; and (b) adequate seating and at least one (1) table for folding clothes. For developments containing more than one hundred (100) rental units that also provide washer and dryer hookups in all units, a minimum of one (1) commercial washer and one (1) commercial dryer per thirty-two (32) units is required. Single family detached unit, townhouse, or duplex developments must provide a washer and dryer hookup in every unit. Developments providing washers and dryers in all rental units are not required to provide a laundry facility.
- 15. Each unit must be equipped with a 5 lb. ABC rated dry chemical fire extinguisher readily accessible in the kitchen and mounted to accommodate handicapped accessible height in accessible units. Fire extinguisher

- must be either clearly visible or if contained in a cabinet/pantry area must have signage identifying location.
- 16. Wall switch controlled Energy Star rated overhead lighting is required in all rooms.
- 17. Sites located in a Radon Zone-1 (highest level) will require Radon Resistant New Construction Practices. Rehabilitation projects must meet the Radon Mitigation Standards as required by the Environmental Protection Agency.
- 18. All new construction developments must submit a complete site specific soils report and boring site plan, not more than one year old at the time of submission of final plans and specifications, bound within the project specifications. Rehabilitation projects adding any new building foundations must submit a foundation specific soils report. The soils report must reflect the results of laboratory tests conducted on a minimum of one (1) soil boring per planned building location and a minimum total of two (2) soil borings at the planned paved areas of the development. A registered professional engineer or a certified testing agency with a current license to practice in the State of South Carolina must prepare the report. Rehabilitation projects adding any new building foundations must also submit a foundation specific soils report and boring site plan.
- 19. Metal flashing or 20 mil polyethylene when used in conjunction with a self- adhering polyethylene laminate flashing, must be installed above all exterior door and window units.
- 20. Mailboxes, playground and all exterior project amenities must be ADA accessible.
- 21. Exterior wall insulation must have an overall R-13 minimum for the entire wall assembly and roof or attic insulation must have an R-30 rating minimum.
- 22. Tub/shower units must have minimum dimensions of 30-inch width by 60-inch length and be equipped with antiscald valves. All shower units without a tub must have minimum dimensions of 36-inch width by 48-length (ADA approved shower). All tubs in designated handicap accessible units must come complete with "factoryinstalled grab bars".
- 23. Mirror length must extend to top of vanity backsplash with top of mirror a minimum of 6'-0" above finish floor. Framed decorative mirrors or medicine cabinets with mirrors are allowed with a minimum size of 14" x 24" and must be hung with the top of mirror a minimum of 6'-0" above finish floor. Vanity cabinets or a medicine cabinet shall be provided in all units. All cabinets in designated handicap accessible units must be installed at ADA mounting heights.
- 24. Water heaters must be placed in drain pans with drain piping plumbed to disposal point as per the latest approved addition of the International Plumbing Code.
- 25. Pipe all Temperature & Pressure (T&P) relief valve discharges to disposal point as per the latest approved edition of the International Plumbing Code.
- 26. Exterior shutters (new not recycled) are required on all 100% vinyl siding buildings. Only existing rehabilitation developments may have 100% vinyl building exteriors.
- 27. Roof gable vents must be made of aluminum or vinyl materials.
- 28. All attics must be vented.
- 29. Carpet and Resilient flooring materials must meet minimum FHA standards.
- 30. Each bedroom and hallway, etc. must have, as required by Code (local, state or Federal) a hard-wired battery back-up smoke detector.
- 31. All materials for construction must meet all local, state, and federal and environmental regulations and specifications.
- 32. A carbon monoxide detector must be installed in each unit with gas mechanical systems or gas appliances. Units with an attached garage must also have a carbon monoxide detector installed. A combination unit smoke detector and carbon monoxide detector can be used to meet this requirement.
- 33. Pre-finished fascia and soffits must be vinyl covered aluminum and/or perforated cementitious panels with vents.
- 34. Gutter and downspout systems complete with splash blocks will be supplied surrounding all residential buildings.
- 35. Gazebos, Picnic Shelters, Mail Kiosks, etc.: Exposed components used as part of the structure must be constructed so that no wood is exposed. Concealment shall be with materials such as aluminum or vinyl siding or cementitious materials. Decorative rails and/or guard rail systems used shall be code compliant systems of vinyl, fiberglass or metal. Wood railings are not allowed. Gazebos and picnic shelters shall have table and bench seating.
- 36. At a minimum, all development must meet the 2006 International Energy Conservation Code.
- 37. Developments that have units, by bedroom size, smaller than the following square footages are considered to be obsolete units and are not eligible for funding:

Bedrooms per Unit	Minimum Sq. Ft. per Unit	
One	500	
Two	700	
Three	850	
Four	1,000	

For All New Construction Developments:

- 1. All units must be equipped with an Energy Star rated dishwasher and an Energy Star rated hot water heater with an energy factor of 0.61 for gas or 0.93 for electric. Submit manufacturer's date sheet with plans.
- 2. All units must have Energy Star rated windows. Submit manufacturer's data sheet with plans.
- 3. All units must have an Energy Star rated HVAC system. Submit manufacturer's data sheet with plans.
- 4. Lighting must be in all common area corridors, stairwells, and the community room. Interior light fixtures to be fitted with Energy Star light bulbs.
- 5. Low flow water saving features must be used- low flow showerheads, low flow kitchen and bathroom faucets, and low flow toilets. Submit manufacturer's data sheet with plans.
- 6. Washer/dryer hookups in all units.
- 7. A minimum 1200 square foot community building to include a kitchen/break room area equipped with, at a minimum, a sink and refrigerator and either a stove/microwave. Entire facility must be ADA compliant. The square footage counted towards this total may include a leasing office, an equipped exercise room, and an equipped computer center. Laundry rooms and storage/maintenance rooms will not be counted as part of the 1200 square foot minimum. For developments proposing the second phase of a previously completed contiguous tax credit development, the requirement for an additional 1200 square foot community building is waived. However, it is required that laundry facilities be provided to the new phase and must be constructed on the site of the proposed phase. The mandatory laundry facility requirements under Section V. Mandatory Design Criteria, item 14 must be met.
- 8. All units pre-wired for cable television hook-ups in the living room and one (1) per bedroom.
- 9. Units with three (3) or more bedrooms must have a minimum of two (2) full bathrooms.
- 10. The minimum bedroom size for the primary bedroom in each unit must be at least 168 square feet. All other bedrooms must be a minimum 120 square feet. The minimum bedroom square footage excludes the closet space.
- 11. All older persons (55+ years) and elderly developments will be one-story structures, or if greater than one story, all stories will be accessible by elevators.
- 12. All sidewalks and walkways shall be a minimum of 36" in width and made of concrete and shall provide access to all parking spaces, front entryway doors, common amenities and driveways and shall be ADA compliant.
- 13. Sliding glass doors are prohibited.
- 14. Water closets must be centered, at a minimum, 18 inches from sidewalls or vanity/lavatories.
- 15. Public use stairway components, such as stringers, treads, and risers must be constructed from steel or concrete. Handrails and pickets must be constructed from steel or aluminum.
- 16. Patio and porch/balcony components used as part of the building shall have concrete slabs or decks and must be constructed so that no wood is exposed. Concealment shall be with materials such as aluminum or vinyl siding or cementitious materials. Structural wood columns shall be at a minimum 6" x 6" pressure treated columns concealed as noted above with properly sized fiberglass, high density urethane or aluminum columns. Decorative rails and/or guard rail systems used at porches and patios shall be code compliant systems of vinyl, fiberglass or metal. Wood railings are not allowed.
- 17. Wall Framing: Sound proofing or sound batt insulation is required between the stud framing in party walls. A sound rating of STC 54 is required.
- 18. Fluorescent lighting is required in the kitchen.

For All Single Family Townhouse, and Duplex Developments:

- 1. All detached single family homes must contain a minimum of three (3) bedrooms and two (2) full bathrooms.
- 2. All townhouses must contain a minimum of two (2) bedrooms and one and one-half bathroom. At a minimum, a half bathroom must be located on the first floor.
- 3. All duplexes must contain a minimum of two (2) bedrooms and one and one-half bathroom.
- 4. Developments must have concrete driveways, curbing at street and front entry walkways.
- 5. All new construction developments must have a washer and dryer hookup in each unit.
- 6. All HVAC and hot water heaters must be contained within the unit/building. These may not be located in the attic or crawl space.

For All Rehabilitation Developments:

Any of the following mandatory items (not to include repainting of the entire unit) replaced on or after January 1, 2011 are not required to be replaced as part of the rehabilitation.

- 1. Replace and install new flooring in each unit. At a minimum, tile must be VCT or better.
- 2. Entire unit (all rooms and ceilings) must be repainted.
- 3. New bathroom fixtures must be installed to include the following:
 - a) New tub and new shower, re-glazing not allowed. Three piece surround insert is acceptable. All caulking must be replaced.

- b) Replace sink, vanity and plumbing fixtures with new. Vanity to include, at a minimum, a pull out drawer and/or storage area.
- c) New toilet.
- d) Install new re-circulating exhaust fan.
- e) Install new water supply valves.
- 4. New kitchen fixtures must be installed to include the following:
 - a) Dual track sliding drawers.
 - b) New double sink and plumbing fixtures.
 - c) New stove with re-circulating exhaust fan.
 - d) New Energy Star rated refrigerator, with ice maker that is a minimum of 14 cubic feet.
 - e) Install new water supply valves.
- 5. All entry doors must be steel or fiberglass doors that are insulated, paneled, and have a peephole.
- 6. New Energy Star hot water heaters with an energy factor greater than 0.61/gas or 0.93/electric.
- 7. Replace all windows with insulated, double pane glass in either vinyl or aluminum framing.
- 8. All units wired for high speed (broadband) Internet hook-up with at least one (1) centrally located connection port or wireless computer network. All wires to be hidden.
- 9. Units with existing washer/dryer connections must replace and install new water supply fixtures and valves.
- 10. All older persons (55+ years) and elderly acquisition/rehabilitation developments may have more than onestory, provided that existing elevators, receiving regular maintenance, are in good working condition as of the initial Tax Credit Application submittal date and service all upper level rental units. Those developments without existing elevators will be required to install elevators.
- 11. Window blinds and exterior window screens to be replaced.
- 12. Replace all damaged and worn interior doors, jambs, frames, and hardware.

For All Adaptive Reuse Developments:

The definition of "adaptive reuse" is the conversion of an existing non-residential building(s) into a residential building(s). The architect must certify on **Exhibit G** that the development will meet the following requirements:

- 1. A minimum of fifty percent (50%) of the square footage of each existing building(s) must be converted to residential use; and
- If additional buildings/units are constructed to provide additional space, the total square footage of the
 previously existing building(s) must constitute a minimum of fifty percent (50%) of the total square footage of
 the entire development.
- 3. Reseal all asphalt parking and roadway surfaces throughout the development.

13. Over the range mounted microwave oven, with re-circulating fan, in all units.

MARK the appropriate box(es) below, thereby indicating that the development <u>will be</u> designed and constructed incorporating the design criteria selected:

Optional Development Design Criteria:

1. 2	Roof shingles must be architectural style anti-fungal and warranted for a minimum of thirty (30) years. Attic insulation rated at R-38 or higher.
	Energy Star rated HVAC systems (15 SEER or grater) in all units.
4.	All units must have a balcony, sunroom, or patio. A sunroom must contain a minimum of three (3) window panels and have distinct architectural separation from the living room. Patios must be at lease 64 sq. ft. Front porches are not considered patios.
5.	Curbing for paved areas throughout the development site including the parking areas.
6.	Gazebo (Must be covered and have bench seating; must be permanently affixed and constructed in place; be ADA compliant, accessible and contain a minimum of 100 square feet) or covered picnic shelter (must have a table and bench seating and must be ADA compliant and accessible) in an appropriate location.
7.	Irrigation/sprinkler system serving all landscaped areas.
8.	Underground utilities (gas/electric, cable and phone) throughout the development site.
9.	Provide in the community room a minimum of two (2) current updated computer systems, manufactured within the last 12 months, to include new computers, new printers, and a new scanner. The computers must be equipped with high speed Internet service (e.g. broadband or cable).
10	. Each unit must have an Energy Star ceiling fan with light fixture in the living room and all bedrooms. All ceiling fans and overhead lights must connect to wall switches.
11	. Full size Energy Star refrigerator, with ice maker, having a minimum size of eighteen (18) cubic feet.
12	. All units must be pre-wired for high speed (broadband) Internet hook-up with at least one (1) centrally located connection port and connection ports in all bedrooms or wireless computer network.

	14.	All units must hav	re a Range Queen, Fire	Stop, Auto Stop or comparable	extinguishing system over the stove.
		15. A minimum square footage per unit based on the number of bedrooms per unit specified as follows. To qualify, all of the units must meet the minimum square footage per unit. The Authority considers the square footage of an individual unit to be the usable living space measured from the interior wall to interior wall.			
		E	Bedrooms per unit	Minimum Sq. Ft. per Unit	
			One	750	
			Two	950	
				1100 1250	
		<u> </u>	Four	1250	
	16.		oms per unit based on the minimum number of ba		ing to the following. To qualify, all the units
			Bedrooms per unit	Bathrooms per unit	
			One -	One Full	
			Two Three	One Full and One ¾ bath Two Full	
			Four	Two Full and One-Half	
		A minimum eight areas: front of bu	(8) camera video secur ildings, back of building	ity system with at least one (1) s, all levels of breezeways, con	camera monitoring all of the following nmunity room, computer room, rental office,
_			exit roadways, and parking		
				officer, on-site manager or mai	-
		minimum one (1)	permanently anchored	weather resistant bench with ba	
	20. Perimeter fencing extending around all sides of the development site, except the development entrance(s). Chain link fencing not allowed.				
	21.	Development to b	pe built to meet, at a mir	nimum, the Version 3.0 Energy	Star Certification.
	22.				nd is dedicated to the collection and storage rdboard, glass, plastics, and metals.
The	follo	wing Optional D	evelopment Design (Criteria are for rehabilitation	developments only:
		• .	-		
			ar rated dishwashers in		
		fitted with Energy	y Star light bulbs.	-	and all bedrooms. All light fixtures to be
	25.	Provide one and	one-half (1.5) bathroom	s in all units with two (2) or mor	re bedrooms.
	26.	Minimum bedroom excludes the close		in each unit is 120 square feet.	The minimum bedroom square footage
	27.	Provide a minimu	ım 1200 square foot cor	nmunity building excluding laur	ndry and storage/maintenance areas.
			for standard size washe		,
		•	d windows in all units.	, ,	
ш		•		with full size Energy Star refrige	protor with ion maker having a minimum
	30. In all units, existing appliances replaced with full size Energy Star refrigerator, with ice maker, having a minimum size of eighteen (18) cubic feet; and an Energy Star rated dishwasher; and an Energy Star rated hot water heater with an energy factor greater than 0.61/gas or 0.93/electric.				
Dev	elop	ment Criteria:			
	Dev		ew Construction (thresh as at least 32 total units	old): but has no more than 72 total ւ	units.
	Development size- Rehabilitation (choose only one): Development has at least 24 total units and is at or below 88 total units. Development has 89 to 104 total units.				
	Durable construction, with respect to each building, one of the following applies (choose only one): Brick/stone veneer or stucco minimum 60% and remaining exterior fiber cement and/or hardiplank. Brick/stone veneer or stucco minimum 50% and remaining exterior fiber cement and/or hardiplank. Brick/stone veneer or stucco minimum 30% and remaining exterior fiber cement and/or hardiplank. Brick/stone veneer or stucco minimum 50% and remaining exterior siding to be vinyl siding with a thickness of at least .044 mils; or full fiber cement.				

☐ For Adaptive Reuse Developments Only:	
A minimum of fifty percent (50%) of the square footage residential use; and	ge of each existing building(s) must be converted to
If additional buildings/units are constructed to provide addressisting building(s) constitutes a minimum of fifty perdevelopment.	
For proposed Older Persons and Elderly Developments:	
YesNo Development contains all one-story units.	
YesNo Development currently has or will have elevator	service to all upper level units.
Architect and/or Professional Engineer Certification	n:
The undersigned certifies to the South Carolina State Housing Fir (1) the above information is true and correct; (2) the development and applications and optional design criteria as stated in the body professional engineer has reviewed the plans and specifications specifications comply with and the development has been constructions of Section 504 of the Rehabilitation Act, the Fair Hothe American With Disabilities Act, 2010 Americans with Disabilities and any other applicable State or Federal legislation. The understruction of the development will meet, at a minimum, the HUD's Fair Housing Act regulations (24 C.F.R. Part 100 as most etc.): (1) accessible building entrance on an accessible route, (2 areas, (3) usable doors, (4) accessible route into and through the outlets, thermostats and other environmental controls in accessib (7) usable kitchens and bathrooms. The undersigned acknow relied upon by the SCSHFDA and that any misrepresentation undersigned and the Developer both being debarred from programs for a minimum of one (1) year and b) the filing of engineer with the S.C. Department of Labor, Licensing and Relief (1) the source of the state of the service of the ser	ment <u>will be</u> constructed in accordance with the of this certification; and (3) the architect and/or of the development to ensure that such plans and structed to comply with the accessibility and other busing Amendments to the Civil Rights Act of 1968, bilities Act Accessibility Guidelines, local building undersigned further certifies that s/he will verify that be following seven specific requirements based on diffied or explained in guidelines, manuals, Q&A's, 2) accessible and usable public and common use a covered dwelling unit, (5) light switches, electrical ble locations, (6) reinforced walls for grab bars, and ledges that the foregoing certifications will be on, whenever discovered, will result in a) the participation in any Authority administered a complaint against the architect/professional
Firm:	Date:
Ву:	License #:
Its:	_